

# Load Rated



G-209 S-209

Screw pin anchor shackles meet Federal Specification RR-C-271b Type IV Class 1.



G-213 S-213

Round pin anchor shackles meet Federal Specification RR-C-271b Type IV Class 4.


- Working Load Limit permanently shown on every shackle.
- Forged, Quenched and Tempered, with alloy pins.
- Capacities 1/3 thru 150 tons.
- Look for the red color . . . mark of genuine Crosby-Laughlin quality.
- Shackles can be furnished proof tested with certificates to designated standards (i.e., ABS, Lloyds, etc.). Charges for proof testing and certification available upon request.
- Hot Dip Galvanized or Self Colored

## ANCHOR SHACKLES

Working Load Limit (tons)	Nominal Shackle Size (in)	DIMENSIONS (in)								Weight (lbs)	
		Inside Length	Inside Width		Diameter		Tolerance Plus or Minus				
			at Pin	at Bow	Pin	Outside of Eye	Length	Width	213	209	
† 1/3	3/16	7/8	3/8	11/16	1/4	9/16	1/16	1/16	—	.05	
1/2	1/4	1 1/8	1/2	25/32	5/16	11/16	1/16	1/16	.13	.12	
3/4	5/16	17/32	17/32	27/32	3/8	13/16	1/16	1/16	.17	.19	
1	3/8	17/16	21/32	11/32	7/16	31/32	1/8	1/16	.25	.31	
1 1/2	7/16	111/16	23/32	15/32	1/2	11/16	1/8	1/16	.38	.38	
2	1/2	1 7/8	13/16	15/16	5/8	13/16	1/8	1/16	.70	.63	
3 1/4	5/8	2 3/8	1 1/16	1 11/16	3/4	1 9/16	1/8	1/16	1.50	1.38	
4 3/4	3/4	2 13/16	1 1/4	2	7/8	1 7/8	1/4	1/16	2.32	2.25	
6 1/2	7/8	3 5/16	1 7/16	2 9/32	1	2 1/8	1/4	1/16	3.40	3.38	
8 1/2	1	3 3/4	1 11/16	2 11/16	1 1/8	2 3/8	1/4	1/16	5.00	5.32	
9 1/2	1 1/8	4 1/4	1 13/16	2 29/32	1 1/4	2 5/8	1/4	1/16	6.97	6.81	
12	1 1/4	4 11/16	2 1/32	3 1/4	1 3/8	3	1/4	1/16	9.75	9.50	
13 1/2	1 3/8	5 3/16	2 1/4	3 1/2	1 1/2	3 5/16	1/4	1/8	13.25	13.25	
17	1 1/2	5 3/4	2 3/8	3 7/8	1 5/8	3 5/8	1/4	1/8	17.25	17.70	
25	1 3/4	7	2 7/8	5	2	4 5/16	3/4	1/8	29.46	30.38	
35	2	7 3/4	3 1/4	5 3/4	2 1/4	5	3/4	1/8	45.75	45.00	
†55	2 1/2	10 1/2	4 1/8	7 1/4	2 3/4	6	3/4	1/4	—	85.75	

†Furnished in screw pin only.

S-2131



Trawling shackle with thin square head screw pin.

## TRAWLING SHACKLES

Self Colored only

Working Load Limit (tons)	Nominal Shackle Size (in)	DIMENSIONS (in)						Weight (lbs)
		Inside Length	Inside Width at Pin	Diameter		Tolerances Plus or Minus		
				Pin	Outside of Eye	Length	Width	
2	1/2	1 5/8	13/16	5/8	13/16	1/8	1/16	.75
3 1/4	5/8	2	1 1/16	3/4	1 9/16	1/8	1/16	1.24
4 3/4	3/4	2 3/8	1 1/4	7/8	1 7/8	1/4	1/16	2.18
6 1/2	7/8	2 13/16	1 7/16	1	2 1/8	1/4	1/16	3.28

NOTE: Maximum Proof Load is 2.2 times the Working Load Limit or as designated. Minimum Ultimate Strength is 6 times the Working Load Limit.