



SAFE WORKING LOAD (SWL) AT 1/5TH MINIMUM BREAKING LOAD OF ROPES WITH IWRC
 (180 KGf/MM² TENSILE GRADE)
 (1770 N/MM² TENSILE GRADE)


SWL (TONNE)	1.0	1.5	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0	18.0	19.0	20.0	
1 Leg	9mm	11mm	13mm	16mm	18mm	20mm	22mm	24mm	26mm	28mm	28mm	32mm	32mm	32mm	35mm	35mm	36mm	38mm	38mm	40mm	40mm	40mm
2 Leg (90° max)	8mm	10mm	11mm	13mm	16mm	18mm	19mm	20mm	22mm	24mm	24mm	26mm	26mm	28mm	28mm	32mm	32mm	32mm	32mm	35mm	35mm	35mm
2 Leg (120° max)	9mm	11mm	13mm	16mm	18mm	20mm	22mm	24mm	26mm	28mm	28mm	32mm	32mm	32mm	35mm	35mm	36mm	38mm	38mm	40mm	40mm	40mm
3 or 4 Leg (90° max)	8mm	8mm	9mm	11mm	13mm	14mm	16mm	16mm	18mm	19mm	20mm	22mm	22mm	22mm	24mm	24mm	26mm	26mm	26mm	28mm	28mm	28mm
3 or 4 Leg (120° max)	8mm	9mm	11mm	13mm	16mm	16mm	18mm	19mm	22mm	22mm	24mm	24mm	26mm	26mm	28mm	28mm	32mm	32mm	32mm	32mm	32mm	35mm



2 Leg 90° max



3 Leg 90° max



4 Leg 90° max



3 Leg 120° max




4 Leg 120° max

SAFE WORKING LOAD (SWL) AT 1/5TH MINIMUM BREAKING LOAD OF ROPE WITH FIBRE CORE
 (145 KGf/MM² TENSILE GRADE)
 (1420 N/MM² TENSILE GRADE)

SWL (TONNE)	1.0	1.5	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0
1 Leg	12mm	14mm	16mm	20mm	22mm	26mm	28mm	32mm	32mm	36mm	36mm
2 Leg (90° max)	10mm	12mm	14mm	16mm	20mm	22mm	24mm	26mm	28mm	32mm	32mm
2 Leg (120° max)	12mm	14mm	16mm	20mm	22mm	26mm	28mm	32mm	32mm	36mm	36mm



2 Leg (120° max)



2 Leg (90° max)